

ROSCAMAT® USA

PNEUMATIC



eurolinkinc.com

YOUR COMPANY
LOGO & CONTACT
HERE

SALES SUPPORT & SERVICE
(740) 392-0330

Reach

→ 43"

↑ 27"

Capacity

US: #0 - 7/8"

METRIC: M1.6 - M27



ROSCAMAT® 400

Series 400 Vertical

Options

- Vertical (V) or Vertical/Horizontal (VH)
- Automatic Lubrication

EDP	Description	Orientation	Auto Tool Lubrication	Speed RPM
R40000F	Series 400 Vertical	Vertical		90-2100
R41000F	Series 400 Vertical with Lubrication	Vertical	●	90-2100
R44000F	Series 400 Vertical/Horizontal	Vertical/Horizontal		90-2100
R45000F	Series 400 Vertical/Horizontal with Lubrication	Vertical/Horizontal	●	90-2100

Interchangeable Speed Modules*

EDP	Description	Capacity		Adapter Size	Max Torque (ft-lb.)
		Inch	Metric		
R40510F	90RPM Module	5/16" - 7/8"	M8 - M22	#2	66
R40520F	170RPM Module	5/16" - 5/8"	M8 - M22	#2	58
R40530F	300RPM Module	#0 - 3/16"	M1.6 - M14	#1	32
R40540F	550RPM Module	#0 - 1/2"	M1.6 - M12	#1	18
R40550F	750RPM Module	#0 - 3/8"	M1.6 - M10	#1	13
R40560F	1050RPM Module	#0 - 5/16"	M1.6 - M18	#1	9
R40570F	2100RPM Module	Drill up to 5/16" ø		B16	4



*Module required for tapping. Arm & module sold separately.

WWW.ROSCAMATUSA.COM